

PRODUCT DATA SHEET

Enviro Floors Flow Aid

DESCRIPTION:

Enviro Floors Flow Aid is for use in improving the flow of any waterborne coating over a surface by reducing the surface tension.

Flow Aid also assists in greatly reducing rejection and the 'quilting effect' between blocks of parquetry or timber boards from the effect of surface tension reduction and flow and wetting enhancement.

FEATURES:

Provides a major improvement in;

- Rejection resistance (craters and 'fish eyes')
- Flow and levelling (roller or applicator marks, 'quilting' effect especially on parquetry).

To enhance the flow of coatings in situations of;

- Low level contamination of a surface to be coated. However, a coating may flow but adhesion will need to be confirmed if surface has suspect contamination. Coatings can be made to flow but may not adhere !
- Coating over unknown surfaces – again verify adhesion.
- Use of older coatings that have lost some 'wetting' action

DIRECTIONS FOR USE:

Add 1 measure (25 ml) per 5 litres of coating material as a basic dosage. A maximum dosage of 100 ml per 5 L can be used in major rejection situations. – however, verify adhesion is OK.

SHAKE WELL BEFORE USE. Failure to shake well can cause 'pitting' of the coated surface.

Note: whatever level is added into a coat, following coats will require that same level of addition.

Overdosing can cause orange peel effect.

PROPERTIES AND DATA

Ingredients	-	Ionic halogen compound
Colour	-	clear to pale yellow
Odour	-	nil
Density	-	1.00 S.G.
Application	-	Vigorous shake mix of the coating container after addition.
Flammability	-	non flammable waterbased
Stability	-	24 months in sealed containers

SUPERIOR FLOOR COATINGS WHICH LOOK AFTER YOUR HEALTH & ENVIRONMENT

Ph: 07 3293 2020 or Visit our web site on coatit.eco

©2025 COATIT Australia, All Rights Reserved. Enviro Floors® & Enviro Deck® is a registered trademark of COATIT Australia.

File Name: COATIT-Pds-ENVIRO FLOORS Flow Aid.doc.

Page 1 of 2



- Coverage - One 500 ml dispenser bottle will dose 50 Litres of waterborne coating
- Safety - Non hazardous per Worksafe Australia.
- Packaging - 500 ml twin neck bottle with measuring chamber for dispensing

For further information on Toxicology of Surface Coatings, please do not hesitate to contact:

Manufactured By: COATIT

Australian Customers Ph: 07 3293 2020

International Customers Ph: +617 3293 2020

Email: sales@coatit.eco

Web: coatit.eco

Sales Office – David Mowbray

Email: sales@coatit.eco

Technical Centre - sales@coatit.eco

SUPERIOR FLOOR COATINGS WHICH LOOK AFTER YOUR HEALTH & ENVIRONMENT

Ph: 07 3293 2020 or Visit our web site on coatit.eco

©2025 COATIT Australia, All Rights Reserved. Enviro Floors® & Enviro Deck® is a registered trademark of COATIT Australia.

File Name: *COATIT-Pds-ENVIRO FLOORS Flow Aid.doc.*

Page 2 of 2

